



University of British Columbia  
CPSC 111, Intro to Computation  
Jan-Apr 2006  
Tamara Munzner

### Static Methods, Conditionals

#### Lecture 10, Tue Feb 7 2006

based on slides by Kurt Eiselt

<http://www.cs.ubc.ca/~tmm/courses/cpsc111-06-spr>

## Reading

- This week: Chapter 6 all (6.1-6.4)

## News

- Midterm tonight: Tue Feb 7, 18:30 - 20:00
  - Geography 100 & 200
  - Seating by last name
    - A-Kim in 200
    - Kirtz-Z in 100
    - Id card face up on desk
    - Every other seat, sit where exam is laid out
    - Closed book/notes/calculator
- Reminder: no labs or tutorials this week

## Recap: Formal vs. Actual Parameters

- **Formal** parameter: in declaration of class

```
public class Point { //...
    public void setPosition(int x, int y) {
        xCoord = x; yCoord = y;
    }
}
```

- **Actual** parameter: passed in when method is called

```
public class PointTest {
    public static void main(String [] args) {
        //...
        tester.setPosition(3,4);
    }
}
```

## Recap: Scope

- **Variable scope**: block of code it's declared in
  - **block** of code is defined by braces { }
- **Class scope**: accessible to any class member
  - fields accessed by all class methods
- **Local scope**: method parameters and variables declared within method body

## Recap: Shorthand Operators

- Java shorthand
  - `count++`; // same as `count = count + 1`;
  - `count--`; // same as `count = count - 1`;
  - note no whitespace between variable name and operator
- Similar shorthand for assignment
  - `tigers += 5`; // like `tigers=tigers+5`;
  - `lions -= 3`; // like `lions=lions-3`;
  - `bunnies *= 2`; // like `bunnies=bunnies*2`;
  - `dinos /= 100`; // like `dinos=dinos/100`;

## Recap: Data Conversion

### ■ Math in Java: it depends!

```
int a = 1 / 3;           // a is 0
double b = 1 / 3;       // b is 0.0
int c = 1.0 / 3.0;      // Java's not happy
double d = 1.0 / 3.0;   // d is 0.333333333
```

## Recap: Data Conversion

- **Casting**: explicit data conversion
- **Widening**: conversion from one data type to another type with equal or greater amount of space to store value
  - widening conversions safer because don't lose information (except for roundoff)
  - Java will do widening conversions automatically
- **Narrowing**: conversion from one type to another type with less space to store value
  - important information may be lost
  - Java will not do narrowing conversions automatically

## Recap: Automatic Conversion

- Done implicitly if widening
- **Assignment conversion**: converted because value of one type assigned to variable of other type
- **Promotion**: converted because expression contains mixed types

```
double b = 1 / 3;
```

```
int hours_worked = 40;
double pay_rate = 5.25;
double total_pay = hours_worked * pay_rate;
```

## Recap: Static Variables

- **Static variable** shared among all instances of class
  - "belongs" to class, not instances
  - only one copy of static variable for all objects of class
  - thus changing value of static variable in one object changes it for all others objects too!
- Memory space for a static variable established first time containing class is referenced in program

## Recap: Static Methods

- **Static method** "belongs" to the class itself
  - not to objects that are instances of class
  - aka **class method**
- Do not have to instantiate object of class in order to invoke static method of that class
  - Can use class name instead of object name to invoke static method

## Recap: Static Example

```
public class Giraffe {
    private static int numGiraffes;
    private double neckLength;
    public Giraffe(double neckLength) {
        this.neckLength = neckLength;
        numGiraffes++;
    }
    public void sayHowTall() {
        System.out.println("Neck is " + neckLength);
    }
    public static int getGiraffeCount() {
        return numGiraffes;
    }
}
```

## Static Example

```
public class Giraffe {
    private static int numGiraffes;
    private double neckLength;
    public Giraffe(double neckLength) {
        this.neckLength = neckLength;
        numGiraffes++;
    }
    public void sayHowTall() {
        System.out.println("Neck is " + neckLength);
    }
    public return numGiraffes;
    }static int getGiraffeCount() {
```

- using `this` implicit parameter to disambiguate scope

## Calling Static Method Example

```
public class UseGiraffes
{
    public static void main (String[] args)
    {
        System.out.println("Total Giraffes: " +
            Giraffe.getGiraffeCount());
        Giraffe fred = new Giraffe(200);
        Giraffe bobby = new Giraffe(220);
        Giraffe ethel = new Giraffe(190);
        Giraffe hortense = new Giraffe(250);
        System.out.println("Total Giraffes: " +
            Giraffe.getGiraffeCount());
    }
}
```

- Note that Giraffe is class name, not object name!
  - at first line haven't created any Giraffe objects yet

## Static Methods

- Static methods do not operate in context of particular object
  - cannot reference instance variables because they exist only in an instance of a class
  - compiler will give error if static method attempts to use nonstatic variable
- Static method *can* reference static variables
  - because static variables exist independent of specific objects

## Static Methods

```
public class UseGiraffes
{
    public static void main (String[] args)
    {
        System.out.println("Total Giraffes: " +
            Giraffe.getGiraffeCount());
        Giraffe fred = new Giraffe(200);
        Giraffe bobby = new Giraffe(220);
        Giraffe ethel = new Giraffe(190);
        Giraffe hortense = new Giraffe(250);
        System.out.println("Total Giraffes: " +
            Giraffe.getGiraffeCount());
    }
}
```

- Now you know what all these words mean
  - main method can access only static or local variables

## Static Methods in java . Math

- Java provides you with many pre-existing static methods
- Package `java.lang.Math` is part of basic Java environment
  - you can use static methods provided by Math class
  - examples:

```
> Math.sqrt(36)           > Math.random()
6.0                       0.7843919693319797
> Math.sin(90)           > Math.random()
0.8939966636005579       0.4253202368928023
> Math.sin(Math.toRadians(90)) > Math.pow(2,3)
1.0                       8.0
> Math.max(54,70)        > Math.pow(3,2)
70                         9.0
> Math.round(3.14159)    > Math.log(1000)
3                          6.907755278982137
                          > Math.log10(1000)
                          3.0
```

## Objectives

- Understand how static methods work
- Understand how to use conditionals
- Understand how boolean operators work

## Conditional Statement

- **Boolean expression:** test that returns true or false
- **Conditional statement:** choose which statement will be executed next based on boolean expression
- **Example**

```
if (age < 20)
    System.out.println("Really, you look like you are "
        + (age + 5) + ".");
```

## Conditional Example

```
import java.util.Scanner;

public class Feelgood
{
    public static void main (String[] args)
    {
        int age;
        Scanner scan = new Scanner (System.in);
        System.out.println ("Enter your age: ");
        age = scan.nextInt();
        if (age < 20)
            System.out.println("Really, you look like you "
                + "are " + (age + 5) + ".");
        System.out.println ("You don't look a day over "
            + (age - 10) + "!");
    }
}
```

## Conditional Example

```
import java.util.Scanner;

public class Feelgood
{
    public static void main (String[] args)
    {
        int age;
        Scanner scan = new Scanner (System.in);
        System.out.println ("Enter your age: ");
        age = scan.nextInt();
        if (age < 20)
            System.out.println("Really, you look like you "
                + "are " + (age + 5) + ".");
        if (age >= 20)
            System.out.println ("You don't look a day over "
                + (age - 10) + "!");
    }
}
```

## Conditional Example

```
import java.util.Scanner;

public class Feelgood
{
    public static void main (String[] args)
    {
        int age;
        Scanner scan = new Scanner (System.in);
        System.out.println ("Enter your age: ");
        age = scan.nextInt();
        if (age < 20)
            System.out.println("Really, you look like you "
                + "are " + (age + 5) + ".");
        else
            System.out.println ("You don't look a day over "
                + (age - 10) + "!");
    }
}
```

## Conditional In Depth

- Within method, statements usually executed top to bottom
  - one after the other
- Change control flow with conditional statement

```
if (age < 20)
    System.out.println("Really, you look like you are "
        + (age + 5) + ".");
```

- Choice hinges on evaluation of boolean operator

## Boolean Expressions

- Boolean expression: test which returns either true or false when evaluated
  - aka conditional
- Consists of operands and operators, like arithmetic expression
  - but operators only return true or false when applied to operands
- Two different kinds of operators
  - relational
    - sometime split into relational and equality
  - logical

## Relational Operators

- Tests two values (operands)
- Operators
  - == equal
    - returns true if they are equal, false otherwise
    - note: do not confuse this with =
  - != not equal
    - returns true if they are not equal, false otherwise
  - < less than
  - <= less than or equal to
  - > greater than
  - >= greater than or equal to

## Equality Example

```
int a = 3;
int b = 6;
int c = 10;

if (a == b)
    System.out.println("these two values are equal");

if ((b - a) == a)
    System.out.println("b is the same as a");

if (a != b)
    System.out.println("nope!");
```

- Note we can use arithmetic operator inside boolean expression

## Logical Operators

- Way to combine results from relational operators into single test
- AND, OR, and NOT
  - in terms from math or philosophy class
- Operators
  - && logical AND
  - || logical OR
  - ! logical NOT

## Logical AND

- Logical AND of values a and b evaluates to
  - true if both a and b are true
  - false otherwise

a	b	a && b
false	false	false
false	true	false
true	false	false
true	true	true

## Logical OR

- Logical OR of values a and b evaluates to
  - true if either a or b are true
  - true if both are true
  - false otherwise

a	b	a    b
false	false	false
false	true	true
true	false	true
true	true	true

## Logical NOT

- Logical NOT of value a evaluates to
  - true if a is false
  - false if a is true

a	! a
false	true
true	false

## Logical Operator Examples

```
int a = 3;
int b = 6;
int c = 10;

if ((b > a) && (c == 10))
    System.out.println("this should print");

if (!(b > a))
    System.out.println("this should not print");

if !(b > a)
    System.out.println("what happened?");
```

## Logical Operator Examples

- is `!(b > a)` the same as
  - `(a > b)`
  - `(a >= b)`
  - `(b < a)`

Questions?