

#### Applications

- Mobile robots, driver assistance
- Cell phone location or object recognition
- Panoramas, 3D scene modeling, augmented reality
- Image web search, toys, retail, ...

# Local feature matching Torr & Murray (93); Zhang, Deriche, Faugeras, Luong (95)

- Apply Harris corner detector
- Match points by correlating only at corner points
- Derive epipolar alignment using robust least-squares





# Scale-Invariant Local Features



SIFT Features

### **Advantages of invariant local features**

- Locality: features are local, so robust to occlusion and clutter (no prior segmentation)
- Distinctiveness: individual features can be matched to a large database of objects
- Quantity: many features can be generated for even small objects
- Efficiency: close to real-time performance
- Extensibility: can easily be extended to wide range of differing feature types, with each adding robustness



















#### **Distinctiveness of features**

- Vary size of database of features, with 30 degree affine change, 2% image noise
- Measure % correct for single nearest neighbor match



### Detecting 0.1% inliers among 99.9% outliers

- We need to recognize clusters of just 3 consistent features among 3000 feature match hypotheses
- RANSAC would be hopeless!

#### Generalized Hough transform

- Vote for each potential match according to model ID and pose
- Insert into multiple bins to allow for error in similarity approximation
- Check collisions





### **Model verification**

- 1. Examine all clusters with at least 3 features
- 2. Perform least-squares affine fit to model.
- 3. Discard outliers and perform top-down check for additional features.
- 4. Evaluate probability that match is correct



### **3D Object Recognition**





- Only 3 keys are needed for recognition, so extra keys provide robustness
- Affine model is no longer as accurate



## Test of illumination invariance

Same image under differing illumination





273 keys verified in final match







### Robot localization results

Joint work with Stephen Se, Jim Little



- Map registration: The robot can process 4 frames/sec and localize itself within 5 cm
- Global localization: Robot can be turned on and recognize its position anywhere within the map
- Closing-the-loop: Drift over long map building sequences can be recognized. Adjustment is performed by aligning submaps.









