

Topics in Artificial Intelligence (CPSC 532L):

Assignment #1

Due on Monday, January 15, 2017 at 9am PST

In this assignment you will get hands on experience with the basic operations, processing and inner-workings of traditional deep learning libraries. There are many deep learning libraries that allow easy creation of complex neural network architectures. In future assignments, for example, we will use **PyTorch** to do this (other popular ones are Keras, TensorFlow and Theano). However, those libraries in an interest of ease of use often abstract a lot of detail. The basics learned in this assignment will give you hands on experience on how they work under the hood and give you skills necessary to implement new types of layers and whole architectures (if necessary) and to think through corresponding algorithmic and computational issues.

Problem 1 (40 points)

The key to learning in deep neural networks is ability to compute the derivative of a vector function \mathbf{f} with respect to the parameters of the deep neural network. Computing such derivatives as closed-form expressions for complex functions \mathbf{f} is difficult and computationally expensive. Therefore, instead, deep learning packages define computational graphs and use automatic differentiation algorithms (typically backpropagation) to compute gradients progressively through the network using the chain rule.

Let us define the following vector functions:

$$y_1 = \mathbf{f}_1(x_1, x_2) = e^{2x_2} + x_1 \sin(3x_2^2) \quad (1)$$

$$y_2 = \mathbf{f}_2(x_1, x_2) = x_1 x_2 + \sigma(x_2), \quad (2)$$

where $\sigma(\cdot)$ denotes the standard sigmoid function. This is equivalent to a network with two inputs $\mathbf{x} = \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$

and two outputs $\mathbf{y} = \begin{bmatrix} y_1 \\ y_2 \end{bmatrix} = \mathbf{f}(\mathbf{x})$ and a set of intermediate layers (note that bold indicates vectors).

- Draw the computational graph.
- Draw backpropagation graph.
- Compute the value of $\mathbf{f}(\mathbf{x})$ at $\mathbf{x} = \begin{pmatrix} 2 \\ 1 \end{pmatrix}$.
- At $\mathbf{x} = \begin{pmatrix} 2 \\ 1 \end{pmatrix}$, compute Jacobian using forward mode auto-differentiation.
- At $\mathbf{x} = \begin{pmatrix} 2 \\ 1 \end{pmatrix}$, compute Jacobian using backward mode auto-differentiation.

Remember that Jacobian is defined as $\frac{\partial \mathbf{f}}{\partial \mathbf{x}}$.

Problem 2 (60 points)

The second half of the assignment requires Python Jupyter and is distributed as a notebook. All instructions are given in the notebook itself. The assignment does not require any libraries beyond vanilla Python. Once the assignment is done hand in both the written portion and the programming portion using handin. When handing in programming assignment make sure you hand in all the code and the notebook contains the output of executed code.