

CPSC 421: Introduction to Theory of Computing
Practice Problem Set #1, Not to be handed in

1. Let L be a regular language. Let $L' \subseteq L$. Is L' necessarily regular? Why?
2. A language L is called *finite* if it contains finitely many strings. Prove that every finite language is regular.
3. Find regular expressions for the following languages.
 - (a) $\{ w : w \text{ contains the substring } 0101 \}$
 - (b) $\{ w : w \text{ has length at least 3 and its third symbol is a 0} \}$
 - (c) $\{ w : w \text{ starts with a 0 and has odd length, or starts with a 1 and has even length} \}$
 - (d) $\{ w : w \text{ is any string except } 11 \text{ and } 111 \}$

4. Can the following sets of strings be accepted by finite automata? Justify your answers!

- (a) $\{1^n : n \text{ is a prime number}\}$;
- (b) $\{0^{2n}1^{2m} : n \text{ and } m \text{ are integers}\}$;
- (c) $\{x : x \text{ is a binary power of two}\}$;
- (d) $\{x : \text{the center symbol of } x \text{ is a } 1\}$.

5. (A Worked Problem). Let S be a language. Show that $S^* = (S^*)^*$.

Solution: We need to show that $S^* \subseteq (S^*)^*$ and $(S^*)^* \subseteq S^*$. To show that $S^* \subseteq (S^*)^*$, recall that any word in a set is also in the set's Kleene closure. For the other inclusion, suppose that $w \in (S^*)^*$. Then

$$w = w_1 \cdots w_n$$

for some $n \geq 0$, where $w_i \in S^*$ for all $i \in \{1, \dots, n\}$. Since $w_i \in S^*$ for every i , it follows that

$$w_i = w_{i,1} \cdots w_{i,k_i}$$

for some $k_i \geq 0$, where $w_{i,j} \in S$ for all $j \in \{1, \dots, k_i\}$. Then

$$w = w_{1,1} \cdots w_{1,k_1} w_{2,1} \cdots w_{2,k_2} \cdots w_{n,1} \cdots w_{n,k_n},$$

where $w_{i,j} \in S$. That is, w is the concatenation of a finite number of words ($k_1 + \dots + k_n$ words) in S , so by definition of the star operation, $w \in S^*$.

6. Show that the regular sets are not closed under infinite union by producing an infinite family of regular sets whose union is not regular.
7. An *epsilon move* takes place when a finite automaton reads and changes state but does not move its tape head. Does this new operation add power to finite automata? Justify your answer.

8. Let $\Sigma = \{0, 1, +, =\}$ and

$\text{ADD} = \{x = y + z : x, y, z \text{ are binary integers, and } x \text{ is the sum of } y \text{ and } z\}$.

Show that ADD is not regular.

9. We can use closure properties to help prove certain languages are not regular. Start with the fact that the language

$$L_{0^n 1^n} = \{0^n 1^n : n \geq 0\}$$

is not regular. Prove the following languages not to be regular by transforming them, using operations known to preserve regularity, to $L_{0^n 1^n}$:

- (a) $\{0^i 1^j : i \neq j\}$;
- (b) $\{0^n 1^m 2^{n-m} : n \geq m \geq 0\}$.

10. Design an algorithm to determine whether a finite automaton accepts an infinite set. Prove that your algorithm is correct.
11. Exhibit an algorithm that detects whether one finite automaton accepts a subset of the set accepted by another machine. Show that this procedure works.
12. Two states of a finite automaton are said not to be *equivalent* if there is a string which takes one into an accepting state and the other into a rejecting state. How many strings must be checked in order to determine whether two states are equivalent? Develop an algorithm for this.
13. If L is a language, and a is a symbol, then L/a , the *quotient* of L and a , is the set of strings w such that $wa \in L$. For example, if $L = \{a, aab, baa\}$, then $L/a = \{\varepsilon, ba\}$. Prove that if L is regular, so is L/a . That is, the set of regular languages are closed under the quotient operation.

Hint: Start with a DFA for L and consider the set of accepting states.

14. If L is a language, and a is a symbol, then $a \backslash L$ is the set of strings w such that $aw \in L$. For example, if $L = \{a, aab, baa\}$, then $a \backslash L = \{\varepsilon, ab\}$. Convince yourself, but not the grader, that if L is regular, so is $a \backslash L$. This operation is sometimes viewed as a “derivative,” and $a \backslash L$ is written $\frac{dL}{da}$. These derivative apply to regular expressions in a manner similar to the way ordinary derivatives apply to arithmetic expressions. Thus, if R is a regular expression, we shall use $\frac{dR}{da}$ to mean the same as $\frac{dL}{da}$, if $L = L(R)$.

- (a) Show that $\frac{d(R+S)}{da} = \frac{dR}{da} + \frac{dS}{da}$;
- (b) Give the rule for the “derivative” of RS . **Hint:** You need to consider two cases: if $L(R)$ does or does not contain ε . This rule is not quite the same as the “product rule” for ordinary derivatives, but is similar;
- (c) Give the rule for the derivative of a closure; i.e., $\frac{d(R^*)}{da}$;
- (d) Use the rules above to find the “derivatives” of regular expression $(0+1)^*011$ with respect to 0 and 1;
- (e) Characterize those languages L for which $\frac{dL}{d0} = \emptyset$;
- (f) Characterize those languages L for which $\frac{dL}{d0} = L$.

15. Give a family of languages E_n , where each E_n can be recognized by an n -state NFA but requires at least c^n states on a DFA for some constant $c > 1$. Prove that your languages have this property.
16. Show that the set of all binary integers that are the sum of exactly four (no more, no less!) positive squares is a regular set. **HINT:** They are all found by substituting for m and n in the formula $4^n(8m + 7)$.
17. (Challenging) If A is a set of natural numbers and k is a natural number greater than 1, let

$$B_k(A) = \{w : w \text{ is the representation in base } k \text{ of some number in } A\}.$$

Here, we do not allow leading 0s in the representation of a number. For example, $B_2(\{3, 5\}) = \{11, 101\}$ and $B_3(\{3, 5\}) = \{10, 12\}$. Give an example of a set A for which $B_2(A)$ is regular but $B_3(A)$ is not regular. Prove that your example works.

18. (Challenging) Give an algorithm that takes a DFA A and computes the number of strings of length n (for some given n , not related to the number of states of A) accepted by A . Your algorithm should be polynomial in both n and the number of states of A .