

Nonlinear Dimensionality Reduction


Donovan Parks

Overview

- Direct visualization vs. dimensionality reduction
- Nonlinear dimensionality reduction techniques:
 - ISOMAP, LLE, Charting
- A fun example that uses non-metric, replicated MDS

Direct visualization


- Visualize all dimensions



Sources: Chuah (1998), Wegman (1990)

Dimensionality reduction

- Visualize the intrinsic low-dimensional structure within a high-dimensional data space
- Ideally 2 or 3 dimensions so data can be displayed with a single scatterplot




When to use:

- Direct visualization:
 - Interested in relationships between attributes (dimensions) of the data
- Dimensionality reduction:
 - Interested in geometric relationships between data points

Nonlinear dimensionality reduction

- Isometric mapping (ISOMAP)
 - *Mapping a Manifold of Perceptual Observations*. Joshua B. Tenenbaum. Neural Information Processing Systems, 1998.
- Locally Linear Embedding (LLE)
 - *Think Globally, Fit Locally: Unsupervised Learning of Nonlinear Manifolds*. Lawrence K. Saul & Sam T. Roweis. University of Pennsylvania Technical Report MS-CIS-02-18, 2002.
- Charting
 - *Charting a Manifold*. Matthew Brand, NIPS 2003.


Why do we need nonlinear dimensionality reduction?



ISOMAP

- Extension of multidimensional scaling (MDS)
- Considers geodesic instead of Euclidean distances


Geodesic vs. Euclidean distance




Source: Tenenbaum, 1998

Calculating geodesic distances

- Q: How do we calculate geodesic distance?




ISOMAP Algorithm




Modified from: Tenenbaum, 1998

Example: ISOMAP vs. MDS



Example: Punctured sphere

- ISOMAP generally fails for manifolds with holes



+/-s of ISOMAP


- Advantages:
 - Easy to understand and implement extension of MDS
 - Preserves "true" relationship between data points
- Disadvantages:
 - Computationally expensive
 - Known to have difficulties with "holes"

Locally Linear Embedding (LLE)

- Forget about global constraints, just fit locally
- Why? Removes the need to estimate distances between widely separated points
 - ISOMAP approximates such distances with an expensive shortest path search


Are local constraints sufficient? A Geometric Interpretation

- Maintains approximate global structure since local patches overlap




Are local constraints sufficient? A Geometric Interpretation

- Maintains approximate global structure since local patches overlap




LLE Algorithm




Source: Saul, 2002

Example: Synthetic manifolds



Modified from: Saul, 2002

Example: Real face images



Source: Roweis, 2000

+/-'s of LLE

- Advantages:
 - More accurate in preserving local structure than ISOMAP
 - Less computationally expensive than ISOMAP
- Disadvantages:
 - Less accurate in preserving global structure than ISOMAP
 - Known to have difficulty on non-convex manifolds (not true of ISOMAP)

Charting


- Similar to LLE in that it considers overlapping "locally linear patches" (called charts in this paper)
- Based on a statistical framework instead of geometric arguments

Charting the data

- Place Gaussian at each point and estimate covariance over local neighborhood


- Brand derives method for determining optimal covariances in the MAP sense

- Enforces certain constraints to ensure nearby Gaussians (charts) have similar covariance matrices



Find local coordinate systems


- Use PCA in each chart to determine local coordinate system




Connecting the charts

- Exploit overlap of each neighborhood to determine how to connect the charts

- Brand suggest a weighted least squares problem to minimize error in the projection of common points



Example: Noisy synthetic data



Source: Brand, 2003

+/-'s of Charting


- Advantage:
 - More robust to noise than LLE or ISOMAP
- Disadvantage:
 - More testing needed to demonstrate robustness to noise
 - Unclear computational complexity
 - Final step is quadratic in the number of charts

Conclusion: +/-'s of dimensionality reduction

- Advantages:
 - Excellent visualization of relationship between data points
- Limitations:
 - Computationally expensive
 - Need many observations
 - Do not work on all manifolds

Action Synopsis: A fun example

- Action Synopsis: Pose Selection and Illustration. Jackie Assa, Yaron Caspi, Daniel Cohen-Or. ACM Transactions on Graphics, 2005.



Source: Assa, 2005

Aspects of motion

- Input: pose of person at each frame



- Aspects of motion:
 - Joint position
 - Joint angle
 - Joint velocity
 - Joint angular velocity

Source: Assa, 2005

Dimensionality reduction

- Problem: How can these aspects of motion be combined?

- Solution: non-metric, replicated MDS
 - distance matrix for each aspect of motion
 - best preserves rank order of distances across several distance matrices



- Essentially NM-RMDS implicitly weights each distance matrix

Source: Assa, 2005

Pose selection

- Problem: how do you select interesting poses from the "motion curve"?


- Typically 5-9 dimensions

- Assa et al. argue that interesting poses occur at "locally extreme points"




Source: Assa, 2005

Finding locally extreme points



Source: Assa, 2005

Do you need dimensionality reduction?




Source: Assa, 2005

Example: Monkey bars



Source: Assa, 2005

Example: Potential application



Source: Assa, 2005

Critique of Action Synopsis

Pros:

- + Results are convincing
- + Justified algorithm with user study

Cons:

- Little justification for selected aspects of motion
- Requiring pose information as input is restrictive
- Unclear that having RMDS implicitly weight aspects of motion is a good idea

Literature

- Papers covered:
 - *Mapping a Manifold of Perceptual Observations*. Joshua B. Tenenbaum. Neural Information Processing Systems, 1998.
 - *Think Globally, Fit Locally: Unsupervised Learning of Nonlinear Manifolds*. Lawrence Saul & Sam Roweis. University of Pennsylvania Technical Report MS-CIS-02-18, 2002.
 - *Charting a Manifold*. Matthew Brand, NIPS 2003.
 - *Action Synopsis: Pose Selection and Illustration*. Jackie Assa, Yaron Caspi, Daniel Cohen-Or. ACM Transactions on Graphics, 2005.
- Additional reading:
 - *Multidimensional scaling*. Forrest W. Young. Forrest.psych.unc.edu/teaching/p208a/mds/mds.html
 - *A Global Geometric Framework for Nonlinear Dimensionality Reduction*. Joshua B. Tenenbaum, Vin de Silva, John C. Langford, Science, v. 290 no. 5500, 2000.
 - *Nonlinear dimensionality reduction by locally linear embedding*. Sam Roweis & Lawrence Saul. Science v.290 no.5500, 2000.
- Further citations:
 - *Information Rich Glyphs for Software Management*. M.C. Chuah and S.G. Eick, IEEE CG&A 18:4 1998.
 - *Hyperdimensional Data Analysis Using Parallel Coordinates*. Edward J. Wegman. Journal of the American Statistical Association, Vol. 85, No. 411. (Sep., 1990), pp. 664-675.